PRODUCT INFORMATION

Description 12-48V LED Work Light with Flood Beam

Pattern & Mounting Bracket

 Height
 54.10 mm / 2.13 in

 Width
 169.67 mm / 6.68 in

 Depth
 45.21 mm / 1.78 in

ShapeRectangleOuter Lens MaterialPolycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

Mounting Hardware Description (x1) 3/8"-16 x 1.5" Mounting Bolt

Mounting Type Universal Mount

Minimum Operating -40 °C / -40 °F

Temperature


Maximum Operating $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$

Temperature

Connector or WiringIntegral DT04-2PMating ConnectorDeutsch DT06-2SProduct Weight0.71 lbs / 0.32 kgsShipping Weight3.40 lbs / 1.54 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage 12-48V DC **Operating Voltage** 9-60V DC

Transient Spike Protection 330V Peak @ 1 HZ-100 Pulses

Red Wire Positive Black Wire Negative

 Current Draw
 1.00A @ 12V DC (Flood)

 0.50A @ 24V DC (Flood)

 0.30A @ 36V DC (Flood)

 0.25A @ 48V DC (Flood)



REGULATORY STANDARDS COMPLIANCE





Buy America Standards Eco Friendly CISPR 12 IEC IP67

UL Recognized

PHOTOMETRIC SPECIFICATIONS


Raw Lumen Output 675 **Effective Lumen** 485

Output

Candela Output 1,409 **Nominal LED Color** 5000 K

Temperature

Beam Pattern(s) Forward Lighting - Flood (Medium)



APPLICATIONS


























PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



<u>Part Number</u> <u>1603451</u>

12-48V LED Work Light with Vertical Flood Beam Pattern & Mounting Bracket

