

| Input Voltage | Max Load | Brightness Per Tube | Tube Size |
|---------------|----------|---------------------|-------------------------------------|
| 12V DC | 20 tubes | 50-70 lm | 12x.375x.50 in (305 x 10 x 13mm) |

Warranty and Disclaimer

Within One year after the purchase date, the original buyer may return any XKGLOW products that has one or more LEDs that fail to illuminate, due to a defect in materials or workmanship.

Installation of this product must be performed by a licensed professional. Should the failure of the product be the result of damage occurring as a result of improper installation, alteration of the product or an act or omission on the part of the consumer, this warranty is void. XKGLOW Lighting shall not be responsible for any consequential damages which arise from the use and/or installation of the product. If the kit is installed in any manner other than specified, XKGLOW Lighting reserves the right to deny any warranty claims at the discretion of the technical support department. Any product return must include the original packaging, invoice number and a statement of the alleged defect. Upon receipt of the returned product, the company will test the product for defect. If the results of the testing do not support the warranty claim, do not reveal any defect or indicate consumer negligence in the installation and handling of the product, then the product will be returned to you and you will be charged a reshipping fee. If the product is returned from an address within the continental United States, within the first 30 days after purchase, and is found to be defective, XKGLOW Lighting will exchange or refund the original purchase expense. This offer does not extend to the cost for shipping charges on any international packages.

Additional Disclaimer Terms

Please check your local and state laws for the proper use of this product.

- Improper installation of electrical products such as lighting may cause damage to any vehicle or device to which the improperly handled or installed lighting is attached.
- Improperly installed product may cause electrical injury to persons.
- It is recommended that the kit should be installed by a licensed professional.
- XKGLOW assumes no liability for the installation of the product.
- Warranty or liability will not exceed the product purchase price, which shall be buyer's sole and exclusive remedy.


Return/Exchange Procedure

1. Email [xkglow@gmail.com] to notify us of the product issue as well as the item number and name of customer on invoice.
2. We will send you the trouble-shooting guide to fix the issue, or to narrow down which of the component(s) need to be replaced. If the issue still exists, we will ask you to send back the defective items to be replaced.
3. Please send the returned item as instructed, along with claims and a telephone number where you can be reached.
4. After the returned item(s) have been accepted and inspected, we will issue a refund or replace the items ASAP. For refunds, item(s) must be sent to XKGLOW within 14 days from date of purchase. Original shipping charges are not refundable.


We always stand behind our products and are committed to our customers! For questions you may have, please contact xkglow@gmail.com. We normally respond within 24 hours. (Monday-Friday).

Mounting Instructions

- 1. Test all components before mounting:** As shown below, plug all light units together and connect them to the switch. Connect the RED wire to the POSITIVE pole of 12V DC battery. Connect the BLACK wire to the NEGATIVE pole. Turn on the switch and exam all the lights. If the light has any defective issue, please contact us and we will be happy to replace them for you.



- 2. Mount the lights:** Place one LED string on the left side of the pickup truck bed and the other LED string on the right, and connect them with the extension wire. Clean the mounting surface. Use the included 3M double side tape pads to attach the lights to the planned locations. Connect all wires and the switch wiring harness. (You might need to turn on the light to get the best lighting angle and positions before firmly mounting the lights.)
- 3. Secure all wires and connectors:** Use provided wire clips to neatly mount and hide any loose wires. Make sure the wires and light tubes are not touching anything hot or located on moving parts. Locate the ON/OFF switch near the tailgate where it is easy to reach.
- 4. Apply waterproof tape:** Pull the included waterproof tape and securely wrap around all connectors. Once the tape shrinks, it will tightly wrap around the connectors to protect them against water and moisture.
- 5. Connect to 12V DC power:** Firmly connect the wire terminals to the positive and negative poles of the battery.



Note: The switch has a built-in auto-off function. If you forget to turn off the switch, the lights will automatically shut off in 15 minutes.

This kit is designed for a max. of 20 XKGLow Light tubes

Visit www.XKGLow.com to purchase extra lights and accessories.